

K2 POWER ES 165K

2-way component kit



Aluminum chassis new design

- Rigid, antimagnetic with exclusive design for a better excursion

K2 Power sandwich cone

- Dynamic & precise

Separated compact crossover (Tweeter 0 / +3 / - 3 dB/oct)

- Quick install and easy settings

Tweeter:

3 assembly solutions

- Factory location
- Flush
- In oriented pod

Integrated terminal

- More compact

Butyl surround exclusive patent "TMD" (Tuned Mass Damper) with S/N engraved

- Better control, more neutral and linear sound

TKM "M" profile aramid fiber inverted dome tweeter

- High extension in treble
- Smooth and precision

WHAT MAKES THE DIFFERENCE

- Inverted dome "M"-shaped tweeter
- Tweeter easy to install (supplied with accessories)
- 1^{1/4}" [32mm] VC diameter for higher performance

TECHNICAL CHARACTERISTICS

2-way component kit

Diameter: 6^{1/2}" [165mm]

Voice coil diameter: 1^{1/4}" [32mm]

Voice coil height: 0^{9/16}" [15mm]

Motor: Magnet

Tweeter: TKM ["M" profile aramid fiber inverted dome]

Cone: Composite K2 Power "W" sandwich cone

Surround: Tuned Mass Damper (TMD®)

Separated crossover: 6-12/12dB [3kHz]

Tweeter Adjustable level: +3; 0; -3dB/oct

Max. power: 200W

Nom. power: 100W RMS

Sensitivity (2.83V/1m): 90.8dB

Frequency response: 60Hz- 22kHz

Impedance: 4 Ω

Accessories: Supplied grilles



Elite

"HAUTE COUTURE" SOUND



FOCAL
THE SPIRIT OF SOUND