

# IC PSA 165

## Product Data Sheet

Processed aluminum inverted dome tweeter  
**Smoothness and definition without directivity**  
Tilted and rotary mounting  
**Orientation in the driver direction**

Butyl surround  
**Perfect reliability**

Polyglass cone  
**Neutral sound without coloration**

Integrated crossover  
**Easy connection**



### Key points

- High sensitivity
- Shallow mounting depth (49.9 mm)
- Great improvement from original car speakers
- Dynamics and neutrality
- Soundstage orientation

Type	2-way coaxial kit
Woofer	6 <sup>1</sup> / <sub>2</sub> " (165mm)
Voice-coil diameter	1" (25mm)
Voice-coil height	0 <sup>1</sup> / <sub>4</sub> " (7mm)
Magnet	3 <sup>9</sup> / <sub>16</sub> " (90mm)
Tweeter	Aluminum inverted dome tweeter
Integrated crossover	6/6dB/oct
Max. power	140W
Nom. power	70W RMS
Sensitivity (2,83 V/1 m)	93.2dB
Frequency response	60Hz - 20kHz
Accessories	Supplied without grille

**FOCAL** *INSIDE*

Focal' is a trademark of Focal-JMLab' - [www.focal.com](http://www.focal.com) - SCAA190319/1

**FOCAL**  
LISTEN BEYOND